



Multi Spray

Product description

Multi Spray is a high-quality, universal spray with 8-fold action: rust dissolver, lubricant, cleaner, water-repellent, penetrating oil, corrosion resistant, contact spray, shock spray.

Properties

- Aerosol can be used in any angle (360°)
- Cooling and shrinking effect (shock spray)
- Does not contain silicones
- In and outdoor use
- Protects
- Reduces humidity
- Removes dirt and grease
- Rust and corrosion-resistant
- Water-repellent



Applications

- Does not attack rubber, plastics or metals.
- Is corrosion-resistant. Has a penetrating action and a protective film remains after cleaning.
- To be used for machines, roller bearings, axles, cogwheels, conveyer belts, rubber gasket profiles,...

Technical data

Base	Mixture based on mineral oil
Consistency	Liquid
Density	ca. 0.85 g/ml
Viscosity	1 mPa.s
Acidity level	Neutral
Application temperature	+5°C → +35°C
Temperature resistance	-50°C → +190°C
Flashpoint	52°C
Volatile organic compounds (VOC)	84%
Solubility in water	Not soluble

Substrates

- Substrate condition
Clean, free of dust and grease.
- Substrate types
All types of metals and plastics.



Multi Spray

Application method

■ Application method

Surfaces must be cleaned, degreased and dry. Shake can well before use. Spray at a distance of appr. 20 cm of the object. Apply as required. Switch electric installations back on when spray is evaporated. When used as a rust dissolver, wait for 5 to 10 minutes.

Health- and Safety Recommendations

Use only in well-ventilated areas.

In case of contact with eyes, wash immediately with plenty of water.

Dangerous. Respect the precautions for use.

Packaging/Logistics

Colour: Please consult the product catalogue, the Soudal website or a Soudal representative.

Packaging: 400 ml aerosol

Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

Remarks

■ Multi Spray can cause staining on porous surfaces.

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.