



Plastic Sheets



foamaluX
WHITE


BRIGHT WHITE FOAM PVC





FOAMALUX

WHITE is a next generation rigid foam PVC substrate, engineered for use with the new breed of high definition wide format digital printers.



HIGH DEFINITION SUBSTRATE

New levels of image quality, increased print resolutions, six colour imaging, advanced image processing and image smoothing technologies - all delivered in the latest digital technology - demands quality substrates which reproduces the quality output of dazzling images and pin sharp text for the highest quality signs, point of purchase displays and exhibition backdrops. Foamalux White has been developed in consultation with digital equipment manufacturers and ink producers to ensure maximum compatibility with evolving digital technologies.

DELIVERING PHOTOGRAPHIC QUALITY EVERY TIME

Utilising an innovative colour formulation, Foamalux White, contains a finely balanced blend of optical pigmentation to produce a brighter white substrate which optimises reproduction capabilities for outstanding print clarity and quality.

- High quality digital imaging
- Excellent colour reproduction
- Superb output quality
- UV stability in the curing process
- Consistent surface quality and exacting sheet tolerances
- Range of thicknesses from 1-24mm for varying applications
- Range of sheet widths up to 2050mm for wide and super-wide format printers



SUPER SMOOTH

Manufactured to exacting tolerances, the ultra smooth, semi matt surface finish of Foamalux White provides a consistently even, reliable surface for digital printing. The flat consistent surface works in harmony with machine calibrations to facilitate faster quality output to maximise productivity.



SUPER STRONG

A uniform, expanded closed cell structure gives Foamalux White a hard, flat surface, providing exceptional rigidity and mechanical properties for intricate die cutting and routing. The durable surface provides excellent resistance to knocks and scratches at the point of display.



SUPER WHITE

A brighter white base material, the colour pigmentation of Foamalux White has been specifically formulated to provide exceptional colour reproduction throughout the spectrum, to achieve maximum stand out for print and display applications. The pigment formulation has been painstakingly innovated to provide the maximum levels of UV stability in the ink curing process to produce outstanding image quality and the highest standards of digital reproduction for demanding colour imaging requirements.



SUPER COMPETITIVE

In today's fast paced, highly-charged print-for-pay marketplace differentiating your company from the competition is critical, the next job depends on the ability to deliver a quality product - on time - today. Foamalux White is a high performance digital substrate, engineered to produce exceptional print quality at cost effective prices time after time after time, resulting in complete satisfaction for the print house and the customer.



FIRE PERFORMANCE

Foamalux White is a self extinguishing material and complies with the most demanding international fire test standards. Contact the Brett Martin technical team for the most up to date information.


SHEET SIZE (mm)	THICKNESS (mm)
1220 x 2440	1, 2, 3, 4, 5, 6, 8, 10, 13, 19 & 24mm
1220 x 3050	1, 2, 3, 4, 5, 6, 8, 10, 13, 19 & 24mm
1560 x 3050	2, 3, 4, 5, 6, 8, 10, 13 & 19mm
2050 x 3050	1, 2, 3, 4, 5, 6, 8 & 10mm



PHYSICAL TEST PROPERTIES

PROPERTY	TEST METHOD	VALUE
Base polymer	-	Polyvinyl Chloride (PVC)
Smell	-	Odourless
Moisture absorption (24 hrs @ 23°C)	DIN 53495	<0.25 % by weight
Water solubility	DIN 53122	Insoluble
Oxygen index	-	49 %
Tensile strength at yield	DIN 53455	16 MPa
Modulus of elasticity	DIN 53457	0.85 MPa - 0.9 MPa
Elongation at break	DIN 53455	27% - 29 %
Flexural strength	DIN 53452	25 MPa - 27 MPa
Impact resistance (Charpy test, un-notched)	DIN 53453	15 kJ/m ²
Shore hardness (3 mm)	DIN 53505	45 - 65
Vicat softening temperature	DIN 53460	76°C
Thermal conductivity, K	DIN 52612	0.085 W/m°C
U value (3 mm)	-	4.8 W/m ² /K
U value (5 mm)	-	4.4 W/m ² /K
Thermal decomposition temperature	-	>200°C
Thermal resistance, R (3 mm)	CEN 492	0.20 m ² K/W
Thermal expansion coefficient	DIN 53752	0.068 mm/m°C
Service temperature range	-	-20 to +60°C
Dielectric strength	DIN 53481	~100 kV/cm
Surface resistance	DIN 53482	>10 ¹² Ω
Volume resistivity	DIN 53482	4 x 10 ¹⁵ Ω cm
Dielectric constant (1 kHz)	DIN 53483	2.4
Dielectric dissipation factor (1 kHz)	DIN 53483	0.013
Comparative Tracking Resistance	DIN IEC 112	600 V
Sound attenuation (3 mm) (100-3500 hz)	-	19dB

DOWNLOAD
OUR FREE APP



Brett Martin's plastic sheet product range includes extensive options in foam PVC, polycarbonate, PVC, acrylic, aPET, PETg, SAN and styrene.



Plastic Sheets

Head Office and Global Sales
Brett Martin Plastic Sheets
24 Roughfort Road
Mallusk, Co. Antrim
Northern Ireland
BT36 4RB

Tel: +44 (0) 28 9084 9999
Fax: +44 (0) 28 9083 6666
Email: mail@brettmartin.com

For the latest information visit the company's web site:
www.brettmartin.com



Q09125

All reasonable care has been taken in the compilation of the information contained within this literature. All recommendations on the use of our products are made without guarantee as conditions of use are beyond the control of Brett Martin. It is the customer's responsibility to ensure that the product is fit for its intended purpose and that the actual conditions of use are suitable. Brett Martin pursues a policy of continuous product development and reserves the right to amend specifications without prior notice. Foamalux® is a registered trademark of Brett Martin Ltd.